



72 x 72mm

**Features:**

- Single row, 3 digit
- Analog style bargraph indication
- True RMS measurement
- For 3 Ø- 4 wire, 3 Ø- 3 wire electrical connection
- Page selection using selector switch

Certifications: CE LISTED

**Display Specifications**

Type of Display	Single row, Liquid Crystal Display
Digits	3
Digit Height	0.56" (14.2mm)
Display Range	0 – 516V
Bargraph	Analog style bargraph indication


**Mechanical Specifications**

Mounting	Panel mount
Weight	206g


**Input Specifications**

Electrical Connection	3 Ø- 4 wire, 3 Ø- 3 wire
Input Type	AC
Input Voltage Range	50-480V
Continuous Max. Input Rating	516V
Overrange Indication	"Or" for input > 516V
Frequency	50 / 60Hz
Resolution	1V
Accuracy	±0.5% of F.S
Input Impedance	1MΩ (± 5%)
Sampling Rate	3 samples / second
Dielectric withstand Voltage	2kV AC between auxiliary supply & measuring input
Rated Impulse withstand Voltage	2kV (1.2/50µS)

**Dimensions**



**Terminal Connections**



**Auxiliary Supply Specifications**

Auxiliary Supply	240V AC ±20%, (50 / 60Hz) 110V AC ±20%, (60Hz)
Power Consumption	5VA max

**Environmental Specifications**

Temperature	Operating: -10°C to +55°C Storage: -20°C to +75°C
Humidity (non-condensing)	Upto 95% RH

## Compliance

Applicable EMI / EMC Standards		
Product Standard : IEC 61326-1		
Category		Standards Compliance
ESD Immunity	IEC 61000-4-2	Level IV (Air discharge : 15kV), (Contact Discharge : -8kV)
Surge Immunity	IEC 61000-4-5	+/- 2kV common mode, (Line to ground) +/- 1kV differential mode, (Line to Line)
Radiated Susceptibility	IEC 61000-4-3	Level III, 80 to 1000MHz (10V/m) Level II, 1.4GHz to 2GHz (3V/m) Level I, 2GHz to 2.7GHz (1V/m)
Conducted Susceptibility	IEC 61000-4-6	Level II (3V/m)
Voltage Dips and Interruptions	IEC 61000-4-11	<b>Dips</b> : 0% residual voltage / 1 cycle (Criteria B), 40% residual voltage / 10 cycles 50Hz / 12 cycles 60Hz (Criteria C) 70% residual voltage / 25 cycles 50Hz / 30 cycles 60Hz (Criteria C) <b>Interruptions</b> : 0% residual voltage / 250 cycles 50Hz / 300 cycles 60Hz (Criteria C)
Conducted Emission	CISPR-11	
Radiated Emission	CISPR-11	
Electrical Fast Transient	IEC 61000-4-4	Level III (2kV)

## Ordering Information

Product Code	Supply Voltage		Certification	
	110V AC	240V AC	CE	UL LISTED
MV2307		■		
MV2307-CU		■	■	■
MV2307-110V	■			
MV2307-110V-CU	■		■	■