CERTIFICATE OF COMPLIANCE

Certificate Number Report Reference Issue Date 20121012-E253771 E253771-A6-UL 2012-OCTOBER-12

Issued to: SELEC CONTROLS PVT LTD ANSA INDL ESTATE, E121/120/113 SAKI VIHAR ROAD,ANDHERI(E) MUMBAI MH 400072 INDIA.

This is to certify that representative samples of

at MEASURING, TESTING AND SIGNAL-GENERATION of EQUIPMENT Components See Addendum page

Have been investigated by UL in accordance with the Standard(s) indicated on this Certificate.

 Standard(s) for Safety:
 UL 61010-1, (Electrical Equipment for Measurement, Control, and Laboratory Use; Part 1: General Requirements) CAN/CSA-C22.2 No. 61010-1, (Electrical Equipment for Measurement, Control, and Laboratory Use; Part 1: General Requirements)

 Additional Information:
 See the UL Online Certifications Directory at www.ul.com/database for additional information

Only those products bearing the UL Listing Mark for the US and Canada should be considered as being covered by UL's Listing and Follow-Up Service meeting the appropriate requirements for US and Canada.

The UL Listing Mark for the US and Canada generally includes: the UL in a circle symbol with "C" and

"US" identifiers: ^(U) the word "LISTED"; a control number (may be alphanumeric) assigned by UL; and the product category name (product identifier) as indicated in the appropriate UL Directory.

Look for the UL Listing Mark on the product.

William R. Carney

William R. Carney, Director, North American Certification Programs



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, pleas contact a local UL Customer Service Representative at <u>www.ul.com/contactus</u> This is to certify that representative samples of the product as specified on this certificate were tested according to the current UL requirements.

Digital Panel Meter-Model MFM384, MFM374 followed by alphabet -C for communication board or/and followed by Five (5) digit Alpha numeric characters based on the asthetic and display features and -CU for UL approved products Model MFM383A followed by Five (5) digit Alphanumeric characters based on the asthetic and display features and -CU for UL approved products. Model EM368 followed by alphabet -C for communication board or/and followed by Five (5) digit Alpha numeric characters based on the asthetic and display features and – CU for UL approved products With and without battery backup display