

l : 230V AC

**Input contact**

XU : 2C/O (DPDT).

XC : 2C/O (DPDT).

ES : 1C/O (SPDT).

IM : 2C/O (DPDT).

Q : 1C/O (SPDT) or  
2C/O (DPDT) (Factory Set)

**Load rating**

5A @ 230V AC / 24V DC, Resistive

**Power Consumption**

XC : 3 VA max

: 6 VA max

8 VA max

ON Delay	OFF
Interval	ON

				OFF
				ON
		ON	OFF	ON
		ON	OFF	ON
		ON	ON	OFF
		ON	ON	ON
1hr	OFF	OFF	ON	OFF/ON
3hr	OFF	ON	ON	OFF/ON
10hr	ON	OFF	ON	OFF/ON
30hr	ON	ON	ON	OFF/ON

**Dip switch settings for mode selection**

MODE	SW5
ON Delay	OFF
Interval	ON

Switch setting example :  
RANGE : 30sec.  
MODE : On delay

**Switch settings for mode selection**

MODE	SW4	SW5
OFF First	ON	ON
ON First	OFF	ON

Switch setting example :  
OFF timer  
ON timer  
MODE



(Specific  
continuous)

**Selec Controls Pvt. Ltd., India.**  
Tel: 91-22-28476442 Fax: 91-22-28476443