OPS2x3-40 | OPEN FRAME POWER SUPPLIES - SELEC



Features :

- 3 x 2 x 1.16 Inches Form Factor
- 40 Watts Convection
- No Load Power < 0.5 W
- - 40°C to + 70°C Operating Temperature
- Efficiencies up to 86 %
- Class II Option Available
- Medical (BF) Safety Approvals
- Approved to Household, ITAV and Medical Standards

SPECIFICATIONS:

MODEL		OPS2x3-40-05	OPS2x3-40-12	OPS2x3-40-15	OPS2x3-40-24	OPS2x3-40-48
	NOMINAL DC VOLTAGE	5 V	12 V	15 V	24 V	48 V
	RATED CURRENT (CONVECTION)	5 A	3.34 A	2.67 A	1.67 A	0.84 A
	RATED CURRENT (FORCED AIR)	NA	NA	NA	NA	NA
	RATED POWER (CONVECTION)	25 W	40 W	40 W	40 W	40 W
	RATED POWER (FORCED AIR)	NA	NA	NA	NA	NA
	RIPPLE & NOISE (Max)	< 1.5 % of Vout	< 1 % of Vout	< 1 % of Vout	< 1 % of Vout	< 1 % of Vout
	SET POINT ACCURACY	5.1 V ± 2 %	12.1 V ± 2.5 %	15.1 V ± 2.5 %	24.1 V ± 3 %	48.1 V ± 3 %
OUTPUT	LINE REGULATION			± 0.5 %		
	LOAD REGULATION			±1%		
	TURN ON TIME	< 1 Sec @ 230 VAC & < 3 Sec @ 115 VAC, Full load				
	HOLD UP TIME		≥ 60 ms @ 2	230 VAC & ≥ 10 ms @ 115	VAC, Full load	
	RISE TIME	< 100 ms				
	FAN OUTPUT	Not Available				
	TRANSIENT RESPONSE	Max excursion 5 % for step load change from 50 % to 100 % at 0.1 A / µsec slew rate, 50 % duty cycle, 50 / 60 Hz. Recovery time < 5 msec				
	VOLTAGE RANGE *	90 - 264 VAC(127 - 370 VDC) Note: 90 - 305 VAC operation available on demand.				
	FREQUENCY RANGE	47 - 63 Hz				
	EFFICIENCY @ 230V AC	Up to 81 %	Up to 83 %	Up to 83 %	Up to 85 %	Up to 86 %
	AC CURRENT	0.85 A @ 115 VAC; 0.45 A @ 230 VAC				
INPUT	POWER FACTOR	No active PFC is available				
	INRUSH CURRENT	< 60 Amps; Measured at 264 VAC, 25°C Ambient, Cold start				
	LEAKAGE CURRENT	< 300 uA; 264 VAC input				
	TOUCH CURRENT	< 100 uA; 264 VAC input				
	NO LOAD POWER CONSUMPTION		< 0.5 W; 115 VAC input			
	OVERLOAD	> 110 % of rated output current; Hiccup mode; Autorecovery type.				
		> 6.5 VDC	>15 VDC	>18 VDC	>28.5 VDC	> 57 VDC
PROTECTION	OVERVOLTAGE	Hiccup mode; Autorecovery type.				
	OUTPUT SHORT CIRCUIT	Hiccup mode when output is shorted; Autorecovery type.				
	OPERATING TEMP	 - 40°C to + 70°C; De-rate linearly above 50°C from 100 % load at 50°C to 50 % load at 70°C. Note: Only start up guaranteed at - 40°C with specification deterioration. 				
	STORAGE TEMP	- 40°C to + 85°C				
ENVIRONMENT	COOLING	Natural convection cooled				
	HUMIDITY	5 to 95 % RH, Non condensing				
	ALTITUDE	2000 m				
	VIBRATION	Component: 10 ~ 500 Hz, 2 G 10 min. / 1 cycle, Period for 60 min. each along X, Y, Z axes				

Note: *Although power supply will work for the specified DC input voltage range, UL approval is only for the specified AC input voltage range.

OPS2x3-40 | OPEN FRAME POWER SUPPLIES - SELEC

MODEL		OPS2x3-40-05	OPS2x3-40-12	OPS2x3-40-15	OPS2x3-40-24	OPS2x3-40-48
DIELECTRIC WITHSTAND	TEST VOLTAGE	I/P to Earth: 1500 VAC, I/P to O/P: 4000 VAC, O/P to Earth: 1500 VAC				
RELIABILITY	MTBF	> 650K hrs. as per MIL-HDBK-217F (25°C)				
	DIMENSION	Overall : 3" x 2" x 1.16" (L x W x H) ; Height above PCB: 1"				
MECHANICAL	WEIGHT	< 100 gms				
	MOUNTING	Open Frame				


I	Category	
Primary to Secondary	2 x MOPP (Means of Patient Protection)	
Primary to Earth	1 x MOPP (Means of Patient Protection)	IEC 60601-1 Ed 3
Secondary to Earth	1 x MOPP (Means of Patient Protection)	

Connectors details

Ref Des	Description	Туре	Pin number	Function
J1	Input AC connector	Tyco: 640445-3;	1	AC Neutral
		Mates with 647402-3;	2	Not connected
		Pin: 3-647409-1	3	AC Line
	Output DC		1, 2	V1 Negative
	connector		3, 4	V1 Positive
-	Earth*	Mounting holes marked with Earth Symbol	-	Earth

Note: * All the mounting holes marked with Earth symbol must be Earthed.


Mechanical dimensions





Note: 1. This open frame power supply should preferably be mounted horizontally on 4 metal

transport integration point provide provi

De-rating curve







Compliance

Applicable EMI / EMC Standards				
Category	Reference Standards	Testing Level		
Conducted Emission	CISPR32	CLASS B		
Radiated Emission	CISPR32	CLASS A		
Electrostatic Discharge	IEC 61000-4-2	Level 4, Criteria A Level 3, Criteria A		
Radiated Susceptibility	IEC 61000-4-3	Level 3, Criteria B		
Electrical Fast Transient / Burst	IEC 61000-4-4	Level 3, Criteria A		
Surge	IEC 61000-4-5	Level 3, Criteria A		
Conducted Susceptibility	IEC 61000-4-6	Level 3, Criteria B		
Power Frequency Magnetic Field	IEC 61000-4-8	Level 4, Criteria A		
Voltage Dips & Interruption	IEC 61000-4-11	Criteria A & B		
Safety	Approved to IEC / EN / UL 62368-1; IEC / EN 60601-1; IEC / EN 61558			

Ordering information

Product Code	Description	Certification
OPS2x3-40-05-A-1-CU	Open Frame Power Supply with 3 x 2 x 1.16" Form factor, 5 V / 5 A, 25 Watts with Convection Cooling	C WUS
OPS2x3-40-12-A-1-CU	Open Frame Power Supply with 3 x 2 x 1.16" Form factor, 12 V / 3.34 A, 40 Watts with Convection Cooling	C WUS
OPS2x3-40-15-A-1-CU	Open Frame Power Supply with 3 x 2 x 1.16" Form factor, 15 V / 2.67 A, 40 Watts with Convection Cooling	C WUS
OPS2x3-40-24-A-1-CU	Open Frame Power Supply with 3 x 2 x 1.16" Form factor, 24 V / 1.67 A, 40 Watts with Convection Cooling	C WUS
OPS2x3-40-48-A-1-CU	Open Frame Power Supply with 3 x 2 x 1.16" Form factor, 48 V / 0.84 A, 40 Watts with Convection Cooling	C WUS