




72 x 72mm

Features:

- True RMS Measurement
- CT Primary Programmable upto 4000A

Certifications: CE 

Display Specifications

Display	Single row, 7 segment LED Display
Digits	4
Digit Height	0.56" (14.2mm)
Display Range	0-4960A

Input Specifications

Electrical Connection	1 Ø-2 wire
Input Type	AC
Input Current Range	50mA - 5A
Continuous Max. Input Rating	6.2A
Ovrerange Indication	"Or" for input > 6.2A
Frequency	50 / 60Hz
Resolution	0.001, 0.01, 0.1, 1A (Depending upon CT Primary Setting)
Accuracy	±0.5% of CT Primary Setting
Input Burden	0.5 VA at 5A
Sampling Rate	3 samples / second
Dielectric withstand Voltage	2kV AC between auxiliary supply & measuring input
Rated Impulse withstand Voltage	3.5kV (1.2/50µS)

Auxiliary Supply Specifications

Auxiliary Supply	240V AC ±20%, (50 / 60Hz) 110V AC ±20%, (60Hz)
Power Consumption	5VA max

Settable Parameters

CT Primary	5,10, 20, 30, 40, 50, 60, 75, 80, 100, 150, 200,250,300,400, 500, 600, 800, 1000,1200, 1500, 1600, 2000, 2500, 3000, 4000
CT Secondary	5A Fixed

Environmental Specifications

Temperature	Operating: -10 to +55°C (14 to 131°F) Storage: -20 to +75°C (-4 to 167°F)
Humidity (non-condensing)	Upto 95% RH

Mechanical Specifications

Mounting	Panel mount
Weight	180 gms (0.418 lbs)


Compliance

Applicable EMI / EMC Standards


Product Standard : IEC 61326-1

Category		Standards Compliance
ESD Immunity	IEC 61000-4-2	Level IV (Air discharge : 15kV), (Contact Discharge : -8kV)
Surge Immunity	IEC 61000-4-5	+/- 2kV common mode, (Line to ground) +/- 1kV differential mode, (Line to Line)
Radiated Susceptibility	IEC 61000-4-3	Level III, 80 to 1000MHz (10V/m) Level II, 1.4GHz to 2GHz (3V/m) Level I, 2GHz to 2.7GHz (1V/m)
Conducted Susceptibility	IEC 61000-4-6	Level II (3V/m)
Voltage Dips and Interruptions	IEC 61000-4-11	Dips : 0% residual voltage / 1 cycle (Criteria B), 40% residual voltage / 10 cycles 50Hz / 12 cycles 60Hz (Criteria C) 70% residual voltage / 25 cycles 50Hz / 30 cycles 60Hz (Criteria C) Interruptions : 0% residual voltage / 250 cycles 50Hz / 300 cycles 60Hz (Criteria C)
Conducted Emission	CISPR-11	
Radiated Emission	CISPR-11	
Electrical Fast Transient	IEC 61000-4-4	Level III (2kV)

Dimensions



Terminal Connections



Ordering Information

Product Code.	Supply Voltage	
	240V AC	110V AC
MA202	■	

Note: CT Type - There is an internal CT with CT setting (5-4000A). For current input >5A, external CT is required.

Direct Type - Input is directly connected to the unit.