48 x 48mm

Features :

- **7 Functions**
- **9 Time ranges**
- **4 Digits, 7 segment LED Dual display**
- **LED Status indications: Relay status, Seconds, Minutes, Hours**
- **Dual set point**
- **Batch function**

Certifications: c ® us

Technical specifications

Display	4 digits, 7 segment LED, dual display
LED indication	1: Relay1 2: Relay2, Second, Minutes, Hours
Start input	Gate/ Pulse start (programmable)
Accuracy	±0.05% of F.S. or 50msec (F.S. = Full Scale)
Relay contact	2 C/O SPDT
Contact rating	5A @ 230 VAC
Modes	ON delay, Interval, Cyclic ON first, Cyclic OFF first, Forward - Pause - Reverse, Instantaneous + Delayed Batch
Time ranges	0 - 99.99sec, 0 - 999.9sec, 0 - 9999sec, 0 - 99: 59min: sec, 0 - 999.9min, 0 - 9999min, 0 - 99: 59hr : min, 0 - 999.9hr, 0 - 9999hr
Resolution	0.01sec
Counting direction	Up/ Down
Set point	2
Time setting	By keys on front panel
Reset	Front, Remote, On Power interruption (programmable)
Memory retention	Yes
Configuration lock	Password protected
Supply voltage	90 to 270 VAC/ DC (50/ 60Hz), 24 VAC/ DC
Power consumption	5VAmax
Temperature	Operating: 0 to 50°C (32 to 122°F) Storage: - 20 to 75°C (- 4 to 167°F)
Humidity (non - condensing)	95% RH
Mounting	Panel mount
Weight	175gms

Dual Display, Multifunction Timer

Terminal connections



Dimensions (All are in mm)



MODELS / DIM	A	B	C	D	E	F	G
XT5042	48	48	100	45	7	46	46

Timing diagrams

1. On delay, Interval modes:



2. Instantaneous + Delayed at start pulse:



3. Cyclic ON first, Cyclic OFF first modes:



4. Instantaneous + Delayed at power on:



5. Motor reverse mode:



t1 = On time of relay1, t3 = On time of relay2,
t2 = Pause time

6. Batch mode



Batch mode

7. Typical application of Gate start in ON delay mode :



$t_i + t_o = t$ (set time), t_h = hold time.

8. Typical application of Continuous start and reset in On delay mode:



Compliance

Category	Reference Standards	Testing Level
Electrostatic Discharge	IEC 61000-4-2	Level-3
Electrical Fast Transient / Brust	IEC 61000-4-4	Level-3
Electromagnetic Field	IEC 61000-4-3	Level-3
Surge	IEC 61000-4-5	Level-3
Conducted RF	IEC 61000-4-6	Level-2
Rated Power Frequency	IEC 61000-4-8	Level-4
Voltage Dip/ Short Interruptions	IEC 61000-4-11	Level-3
Conducted Emissions	CISPR-11	Class-B
Rated Emissions	CISPR-22	Class-A
Emission & Immunity	IEC 61326-1	
Safety	IEC 61010-1	
PFMF (Passing criteria)	IEC 61000-4-8	Class A

Ordering information

XT5042	90 to 270 VAC/ DC	
XT5042-CU-ROHS	90 to 270 VAC/ DC	E253771
XT5042-24V	24 VDC	- - -